DESCRIPTIVE REPORT ON STATUS OF COMPLIANCE TO CONDITIONS OF ENVIRONMENT CLEARANCE AND ENVIRONMENT MANAGEMENT

Compliance Status (for the period of (October 2020 – March 2021) of Environmental Clearance issued by MoEFCC, New Delhi vide File no. 10-14/2017-IA-III dated 11.11.2020

(**Detail of project:** "Expansion of the existing jetty capacity from 4.979 MMTPA to 12 MMTPA by setting-up second birth and increasing the storage capacities of the terminal from 8.5 Lakh KL to 17.5 lakh KL by establishing additional tanks with associated facilities at GIDC, Dahej, Taluka Vagra, Dist. Bharuch, Gujarat by M/s Gujarat Chemical Port Terminal Company Limited.

REMARK: Construction activity of the approved expansion project is yet not started.

S.	EC Condition	Compliance Status
No		
Α	SPECIFIC CONDITIONS	
(i)	The Environmental and CRZ Clearance to the project is primarily under provisions of EIA Notification, 2006 and CRZ Notification,2011. It does not tantamount to approvals/consent/permissions etc. required to be obtained under any other Act/Rule/Regulation. The	We have obtained the in-principal approval for Forest Diversion from the Ministry of Environment Forest and Climate Change, Bhopal vide letter No.6-GJC004/2015-BHO/1037 dated 18.08.2015. Copy of the same is attached herewith as an Annexure-A. We have also obtained the in-principal approval from the Gujarat Maritime Board vide letter no. GMB/N/PVT//609/561 dated 03.11.2011. Copy of the same is attached herewith as an Annexure-B.
	Project Proponent is under obligation to obtain approvals/clearances under any other Acts/Regulations or Statutes as applicable to the project.	All other statutory approvals from the concerned authorities will be taken prior to construction of second jetty.
(ii)	The project proponent shall abide by all the commitments and recommendations made in the Form-II, EIA and EMP report, submission made during Public Hearing and also that have been made during their presentation to EAC.	Noted and agreed.
(iii)	Construction activity shall be carried out strictly according to the provisions of the CRZ Notification, 2011. No construction works other than those permitted in Coastal Regulation Zone Notification shall be carried out in Coastal Regulation Zone area.	Construction activity of the approved expansion project is yet not started. No construction works other than those permitted in Coastal Regulation Zone Notification will be carried out in Coastal Regulation Zone area.
(iv)	All the recommendations and conditions specified by the Gujarat Coastal Zone Management Authority (GCZMA) vide letter ENV-10-2018-183-E (T-Cell) dated	Construction activity of the approved expansion project is yet not started. However, all the recommendations and conditions specified by the Gujarat Coastal Zone Management Authority (GCZMA) vide letter ENV-10-2018-183-E (T-Cell) dated 18 th January, 2018 will be complied with.

	18 th January, 2018 shall be complied with.	
(v)	The Project Proponent shall ensure that no creeks or rivers are blocked due to any activities at the project site and free flow of water is maintained. Creek water monitoring program shall be implemented during the construction phase.	Construction activity of the approved expansion project is yet not started. However, it will be ensured that no creeks or rivers are blocked due to any activities at the project site and free flow of water will be maintained.
(vi)	As proposed, the Proponent shall plant for a width of 50 meter along the entire stretch of shore front with endemic species for shore stabilization.	A width of 50 meter greenbelt along the entire stretch of shore front with endemic species for shore stabilization will be developed.
(vii)	As proposed the dredged material shall be used for raising the ground level of 39 Ha. diverted plot and/or disposing the surplus dredge material at GMB approved dredge disposal site. The impact of dredging on the marine environment should be monitored and necessary measures shall be taken on priority basis if any adverse impact is observed.	Dredging work for the expansion project has not been started yet. However, as proposed the dredged material will be used for raising the ground level of 39 Ha. diverted plot and/or disposing the surplus dredge material at GMB approved dredge disposal site. The impact of dredging on the marine environment will also be monitored and necessary measures will also be taken if any adverse impact is observed.
(viii)	Marine ecological monitoring and its mitigation measures for protection of phytoplankton, zooplanktons, macrobenthos, estuaries, sea-grass, algae, sea weeds, Crustaceans, Fishes, coral reefs and mangroves, etc. as given in the EIA-EMP Report shall be complied with in letter and spirit.	Marine ecological monitoring and its mitigation measures for protection of phytoplankton, zooplanktons, macrobenthos, estuaries, sea-grass, algae, sea weeds, Crustaceans, Fishes, coral reefs and mangroves, etc. will be complied with during construction phase and operation phase as given in the EIA-EMP Report.
(ix)	Continuous online monitoring of air and water covering the total area shall be carried out and the compliance report of the same shall be submitted along with the 6 monthly compliance reports to regional office of MoEF&CC.	Construction activity of the approved expansion project is yet not started. Continuous online monitoring system of air and water covering the total area will be installed. Will be Complied with. Further, air and water quality parameters of ambient location and workplace are also being monitored through MoEF&CC recognized and NABL accredited Laboratory – M/s. Kadam Environment Consultants, Vadodara. Half yearly compliance status report of Environment Clearance is regularly submitted to MoEFCC, Bhopal.

(x)	The actions shall be in accordance with the proposed landscape planning concepts to minimize major landscape changes. The change in land use pattern shall be limited to the proposed port limits and be carried out in such a way as to ensure proper drainage by providing surface drainage systems including storm water network.	Construction activity of the approved expansion project is yet not started. Will be complied with.
(xi)	Suitable preventive measures be taken to trap spillage of fuel/engine oil and lubricants from the construction site. Measures should be taken to contain, control and recover the accidental spill of fuel during cargo handling.	 Following provisions will be in place to handle accidental oil spills, if any in environment friendly manner. Terminal area - Centralized and independent oil storage and handling facilities under custody of store department at Terminal premises will be provided with RCC/PCC flooring. Close circuit (OWS – Oily Water System) to transfer oil contaminated washed water/spilled oil, if to ETP. Hand operated pump will be provided to facilitate transfer of oil from barrel in easy and convenient way while ensuring zero spillage. Provision of drip tray for collection and recovery of oil spill, if any for lubricating type machineries. Leakage of hazardous material, if any taking place during tanker movement/shifting, the leaked/leaked product will be collected in drums and stored at hazardous waste storage shed. Dyke wall with drain collection sump equipped with controlled valve operation for bulk storage of hazardous chemicals. Jetty area - Making provision of oil spill combating Equipment regarding – supply and maintenance of Oil Spill Equipment including competent persons to handle Oil Spill, if any is outsourced. Work Order will be awarded to competent agency for providing Tier 1 oil spill response (OSR) as per IMO (International Maritime Organization) on 24 x 7 basis.
(xii)	All the mitigation measures submitted in the EIA report shall be prepared in a matrix format and the compliance for each mitigation plan shall be submitted to the RO, MoEF&CC along with half yearly compliance report.	Construction activities for the expansion project has not been started yet. All the mitigation measures submitted in the EIA report will be prepared in a matrix format before construction activities starts and the compliance for each mitigation plan will be submitted to the RO, MoEF&CC along with half yearly compliance status.
(xiii)	The company shall draw up and implement Corporate Social Responsibility Plan as per the Company's Act of 2013.	GCPTCL conducts CSR (Corporate Social Responsibility) activities based on the needs of the community/population staying in nearby villages – e.g. Lakhigam. During October 2020 to March 2021 following CSR activities were carried out—

SN	Facilities	Evidence – You may please refer	Cost incurre d
1	Construction of Houses for BPL Families (10 + 20 = 30 Houses)	Annexure 19: in the main report letter from Sarpanch —Lakhigram dated 14.10.2020	Rs. 42.02 +Rs. 74.42 = Rs.116. 44 Lakhs
2	Donation to Seva Rural Trust,Jhagadi a for installation of Bio Optical Meter	Annexure 20: Letter dt. 03.10.20 from Sewa Rural trust is attached.	Rs. 30 Lakhs
3	Donation to Civil Hospital for setting up New Born Hearing Centre Services	Annexure 21: Letter dt. 27.11.20 From Gujarat CSR Authority is attached	Rs. 3.42 Lacs
4	Construction of 40 nos. of houses for BPL Families	Annexure 22: Letter dt. 20.10.20 from TDO is attached	Rs. 126 lacs (In progres s)
5	Construction of Sub health Centre at Lakhigam	Annexure 23: Letter dt. 31.12.20 from TDO is attached	Rs. 50 Lacs (In progres s)

The other key CSR activities includes -

- Donation of hearing aids for new born babies at Civil Hospital, Bharuch – 4.32 Lacs
- Donation of State of the art Optical Bio-Meter to SEWA Rural Hospital, Zaghadiya, Bharuch
- Contribution to Deen Special Education Trust 2.50 Lacs
- Play area equipments for 4 schools nearby Lakhigam village
 21.23 Lacs
- Construction of Library building with infrastructure 9.12 Lacs

		Total expenditure incurred as a part of CSR and/or socioeconomic activities during October 2020 to March 2021 was @ INR 3.63 crore.
		COMPLIED.
(xiv)	As per the Ministry's Office Memorandum F. No. 22-65/2017-IA.III dated 30th September, 2020, the project proponent shall abide by all the commitments made by them to address the concerns raised during the public consultation. The project proponent shall initiate the activities proposed by them, based on the commitment made in the public hearing, and incorporate in the Environmental Management Plan and submit to the Ministry. All other activities including pollution control, environmental protection and conservation, R&R, wildlife and forest conservation/protection measures including the NPV, Compensation Aforestation etc. either proposed by the project proponent based on the social impact assessment and R&R action plan carried out during the preparation of EIA report or prescribed by EAC, shall also be	Noted.
	implemented and become	
<u> </u>	part of EMP.	
В	STANDARD CONDITIONS	
(i)	Statutory Compliance Construction activity shall be carried out strictly according to the provisions of CRZ Notification, 2011 and the State Coastal Zone Management Plan as drawn	Construction activities for the expansion project has not been started yet. However, it will be ensured that construction activities to be carried out will be strictly according to the provisions of CRZ Notification, 2011 and the State Coastal Zone Management Plan as drawn up by the State Government.
	up by the State Government. No construction work other than those permitted in Coastal Regulation Zone Notification shall be carried out in Coastal Regulation Zone area.	It will also be ensured that no construction work other than those permitted in Coastal Regulation Zone Notification will be carried out in Coastal Regulation Zone area.
(ii)	A certificate of adequacy of available power from the	Additional Power requirement for the expansion project will be met through Dakshin Gujarat Vij Corporation Limited (DGVCL).

	agency supplying power to the project along with the load allowed for the project should be obtained.		obtained			with allowed construction
(iii)	All other statutory clearances such as the approvals for storage of diesel from Chief Controller of Explosives, Fire Department, Coast Guard, Civil Aviation Department shall be obtained, as applicable by project proponents from the respective competent authorities.	from the Min Bhopal vide 18.08.2015. Annexure-A. We have also Maritime Bo 03.11.2011. Annexure-B.	istry of Enver letter Copy of the obtained the copy of the copy of the copy of the copy of the copy appro-	vironment Fo No.6-GJC00 ne same is ne in-principa etter no. GM ne same is	rest and Clin 4/2015-BHO/ attached he I approval fro MB/N/PVT//60 attached he	rest Diversion nate Change, 1037 dated rewith as an om the Gujarat 109/561 dated rewith as an authorities will
II	Air quality monitoring and preservation				, ,	
(i)	(i) The project proponent shall install system to carryout Ambient Air Quality monitoring for common/criterion parameters relevant to the main pollutants released (e.g. PM ₁₀ and PM _{2.5} in reference to PM emission, and SO ₂ and NO _x in reference to SO ₂ and NO _x emissions) within and outside the project area at least at four locations (one within and	Ambient Air quality monitoring for common/criterion parameters is carried out through MoEF&CC and NABL accredited laboratory M/s. Kadam Environmental Consultants, Vadodara. Summary of Ambient Air Quality Monitoring for the reporting period i.e., (October 2020 to March 2020) is appended as below for ready reference.				
			1			
	reference to SO ₂ and NO _x emissions) within and outside the project area at least at four locations (one within and	Parameter - AAQM	GPCB consent ed limit - µg/m3	Average µg/m3	Minimum µg/m3	Maximu m µg/m3
	reference to SO ₂ and NO _x emissions) within and outside the project area at least at four locations (one within and three outside the plant area at an angle if 120° each),		consent ed limit			m
	reference to SO ₂ and NO _x emissions) within and outside the project area at least at four locations (one within and three outside the plant area at	- AAQM	consent ed limit - µg/m3	µg/m3	μg/m3	m µg/m3
	reference to SO ₂ and NO _x emissions) within and outside the project area at least at four locations (one within and three outside the plant area at an angle if 120° each), covering upwind and	- AAQM	consent ed limit - µg/m3	µg/m3 70.83	μ g/m3 63.67	м µg/m3
	reference to SO ₂ and NO _x emissions) within and outside the project area at least at four locations (one within and three outside the plant area at an angle if 120° each), covering upwind and	PM10 PM2.5	consent ed limit - µg/m3	μg/m3 70.83 20.22	μ g/m3 63.67 13.67	82.00 28.00
	reference to SO ₂ and NO _x emissions) within and outside the project area at least at four locations (one within and three outside the plant area at an angle if 120° each), covering upwind and	PM10 PM2.5 SO2	consent ed limit - µg/m3 100 60 80	μg/m3 70.83 20.22 8.67 12.33 6.92	μg/m3 63.67 13.67 7.52	82.00 28.00 9.34
	reference to SO ₂ and NO _x emissions) within and outside the project area at least at four locations (one within and three outside the plant area at an angle if 120° each), covering upwind and	PM10 PM2.5 SO2 NOx	consent ed limit - µg/m3 100 60 80	μg/m3 70.83 20.22 8.67 12.33 6.92 12.02	μg/m3 63.67 13.67 7.52 11.36	82.00 28.00 9.34 13.10
	reference to SO ₂ and NO _x emissions) within and outside the project area at least at four locations (one within and three outside the plant area at an angle if 120° each), covering upwind and	PM10 PM2.5 SO2 NOx HCL Cl2 CO	consent ed limit - μg/m3 100 60 80 80 200 100 4000	μg/m3 70.83 20.22 8.67 12.33 6.92 12.02 1100.11	μg/m3 63.67 13.67 7.52 11.36 0.25 1.58 957.67	m μg/m3 82.00 28.00 9.34 13.10 15.98 48.94 1252.33
	reference to SO ₂ and NO _x emissions) within and outside the project area at least at four locations (one within and three outside the plant area at an angle if 120° each), covering upwind and	PM10 PM2.5 SO2 NOx HCL Cl2 CO HC	consent ed limit - μg/m3 100 60 80 80 200 100 4000 160	μg/m3 70.83 20.22 8.67 12.33 6.92 12.02 1100.11 N.D.	μg/m3 63.67 13.67 7.52 11.36 0.25 1.58 957.67 N.D.	m μg/m3 82.00 28.00 9.34 13.10 15.98 48.94 1252.33 N.D.
	reference to SO ₂ and NO _x emissions) within and outside the project area at least at four locations (one within and three outside the plant area at an angle if 120° each), covering upwind and	PM10 PM2.5 SO2 NOx HCL Cl2 CO HC NH3	consent ed limit - μg/m3 100 60 80 80 200 100 4000 160 400	μg/m3 70.83 20.22 8.67 12.33 6.92 12.02 1100.11 N.D. 5.92	μg/m3 63.67 13.67 7.52 11.36 0.25 1.58 957.67 N.D. 3.53	m μg/m3 82.00 28.00 9.34 13.10 15.98 48.94 1252.33 N.D.
	reference to SO ₂ and NO _x emissions) within and outside the project area at least at four locations (one within and three outside the plant area at an angle if 120° each), covering upwind and	PM10 PM2.5 SO2 NOx HCL Cl2 CO HC NH3 H2S	consent ed limit - μg/m3 100 60 80 80 200 100 4000 160 400 500	μg/m3 70.83 20.22 8.67 12.33 6.92 12.02 1100.11 N.D. 5.92 N.D.	μg/m3 63.67 13.67 7.52 11.36 0.25 1.58 957.67 N.D. 3.53 N.D.	m μg/m3 82.00 28.00 9.34 13.10 15.98 48.94 1252.33 N.D. 9.24 N.D.
	reference to SO ₂ and NO _x emissions) within and outside the project area at least at four locations (one within and three outside the plant area at an angle if 120° each), covering upwind and	PM10 PM2.5 SO2 NOx HCL Cl2 CO HC NH3	consent ed limit - μg/m3 100 60 80 80 200 100 4000 160 400	μg/m3 70.83 20.22 8.67 12.33 6.92 12.02 1100.11 N.D. 5.92	μg/m3 63.67 13.67 7.52 11.36 0.25 1.58 957.67 N.D. 3.53	m μg/m3 82.00 28.00 9.34 13.10 15.98 48.94 1252.33 N.D.

		Note – reference method of analysis is indicated in the report and ND = Not Detectable.
		Report of Ambient Air Quality Monitoring for the reporting period is attached as an Annexure 29 .
(ii)	Appropriate Air Pollution Control (APC) system shall be provided for all the dust generating points including fugitive dust from all	There are no production activities involved in the project. Air pollution from the project is less likely to be occur. However, to control the dust and fugitive emission following steps will be taken:
	vulnerable sources, so as to comply prescribed emission standards.	 Water sprinkling will be carried out to supress fugitive dust during earthworks and along unpaved sections of access roads. The storage tanks will be provided with proper sealing system
		 for minimizing fugitive emissions. Pump with double mechanical seal will be used while handling liquid hydrocarbons.
		 Adequate stack height will be provided to DG Set. The vehicular emission from the tankers is expected to be low as the terminal is planned in such a way that once the tanker enters the terminal area its fast turnaround is ensured due to less distance, adequate space, quick connect, disconnect and automation.
		 Closed and mechanized loading/unloading will be provided. Periodic monitoring of ambient air quality will also be carried out through competent agencies.
(iii)	Shrouding shall be carried out in the work site enclosing the dock/proposed facility area. This will act as dust curtain as well achieving zero dust discharge from the site. These curtain or shroud will be immensely effective in restricting disturbance from wind in affecting the dry dock operations, preventing waste dispersion, improving working conditions through provision of shade for the workers.	Shrouding will be carried out in the work site enclosing the dock/proposed facility area during construction phase of the expansion project.
(iv)	Dust collectors shall be deployed in all areas where blasting (surface cleaning) and painting operations are to be carried out, supplemented by stacks for effective dispersion.	Dust collectors supplemented by stack for effective dispersion will be deployed in all areas where blasting (surface cleaning) and painting operations will be carried out.
(v)	The Vessels shall comply the emission norms prescribed from time to time.	Noted and agreed.
(vi)	Diesel power generating sets proposed as source of backup power should be enclosed type and conform to rules made under the	Diesel power generating sets proposed as source of backup power will be enclosed type and conforming to rules made under the Environment (Protection) Act, 1986 and will be installed after consultation with GPCB.

management and traffic decongestion plan shall be drawn up to ensure that the current level of service of the roads within a 05 kms radius of the project is maintained and improved upon after the implementation of the project. This plan should be based on cumulative impact of all development and increased habitation being out or proposed to be carried out by the project or other agencies in this 05 kms radius of the site in different scenarios of space and time and the traffic management plan shall be duly validated and certified by the State Urban Development department and the P.W.D./competent authority for road augmentation and shall also have their consent to the implementation of components of the plan which involve the participation of these departments. III Water quality monitoring and ensure that no creeks or rivers are blocked due to any activities at the project site and free flow of water is maintained. (ii) Appropriate measures must be taken while undertaking digging activities to avoid any likely degradation of water quality. Sitt curtains shall be used to contain the spreading of suspended sediment of suspended sediment of suspended sediment of the project site and free flow of water unall level of the project site and free flow of water will adopted. Following mitigation measures will be taken while undertaking digging activities to avoid any likely degradation of water quality. Sitt curtains shall be used to contain the spreading of suspended sediment of suspended		l = 1	[]
DG sets should be equal to the height needed for the height needed for the combined capacity of all proposed DG sets. Use of low sulphur diesel. The location of the DG sets may be decided with in consultation with State Pollution Control Board. (vii) A detailed traffic management and traffic decongestion plan shall be drawn up to ensure that the current level of service of the roads within a 05 kms radius of the project is maintained and improved upon after the implementation of the project. This plan should be based on cumulative impact of all development and increased habitation being out or proposed to be carried out by the project or other agencies in this 05 kms radius of the site in different scenarios of space and time and the traffic management plan shall be duly validated and certified by the State Urban Development department and the P.W. D/competent authority for road augmentation and shall also have their consent to the implementation of components of the plan which involve the participation of these departments. III Water quality monitoring and preservation (ii) The Project proponent shall ensure that no creeks or rivers are blocked due to an activities at the project site and free flow of water is maintained. Following mitigation measures will be taken while undertaking digging activities to avoid any likely degradation of water was activities at the project site and efficient construction techniques will superiod of maintained. Following mitigation measures will be taken while undertaking digging activities to avoid any likely degradation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment sefficient construction techniques will supported.			
the height needed for the combined capacity of all proposed DG sets. Use of low sulphur diesel. The location of the DG sets may be decided with in consultation with State Pollution Control Board. (vii) A detailed traffic management and traffic decongestion plan shall be drawn up to ensure that the current level of service of the roads within a 05 kms radius of the project is maintained and improved upon after the implementation of the project. This plan should be based on cumulative impact of all development and increased habitation being out or proposed to be carried out by the project or proposed to be carried out by the State Urban Development department and the P.W.D./competent authority for road augmentation and shall also have their consent to the implementation of the project site and free flow of water is maintained. (ii) Appropriate measures must be taken while undertaking digging activities to avoid any likely degradation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment			·
combined capacity of all proposed DG sets. Use of low sulphur diesel. The location of the DG sets may be decided with in consultation with State Pollution Control Board. (vii) A detailed traffic management and traffic decongestion plan shall be drawn up to ensure that the current level of service of the roads within a 05 kms radius of the project is maintained and improved upon after the implementation of the project. This plan should be based on cumulative impact of all development and increased habitation being out or proposed to be carried out by the project or other agencies in this 05 kms radius of the site in different scenarios of space and time and the traffic management plan shall be duly validated and certified by the State Urban Development department and the P.W.D./competent authority for road augmentation and shall also have their consent to the implementation of components of the plan which involve the participation of these departments. (ii) The Project proponent shall ensure that no creeks or rivers are blocked due to any activities at the project site and free flow of water is maintained. (iii) Appropriate measures must be taken while undertaking digging activities to avoid any likely degradation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment		-	sets.
proposed DG sets. Use of low sulphur diesel. The location of the DG sets may be decided with in consultation with State Pollution Control Board. (vii) A detailed traffic decongestion plan shall be drawn up to ensure that the current level of service of the roads within a 05 kms radius of the project is maintained and improved upon after the implementation of the project. This plan should be based on cumulative impact of all development and increased habitation being out or proposed to be carried out by the project or other agencies in this 05 kms radius of the site in different scenarios of space and time and the traffic management plan shall be duly validated and certified by the State Urban Development department and the P.W.D./competent authority for road augmentation of the project site and shall also have their consent to the implementation of components of the plan which involve the participation of these departments. III Water quality monitoring and preservation (i) The Project proponent shall ensure that no creeks or rivers are blocked due to any activities at the project site and free flow of water will maintained. (ii) Appropriate measures must be taken while undertaking digging activities to avoid any likely degradation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment for the efficient techniques will recue the period of impact.			
sulphur diesel. The location of the DG sets may be decided with in consultation with State Pollution Control Board. (vii) A detailed traffic acongestion plan shall be drawn up to ensure that the current level of service of the roads within a DS kms radius of the project is maintained and improved upon after the implementation of the project. This plan should be based on cumulative impact of all development and increased habitation being out or proposed to be carried out by the project or other agencies in this 05 kms radius of the site in different scenarios of space and time and the traffic management plan shall be duly validated and certified by the State Urban Development department and shall also have their consent to the implementation of components of the plan which involve the participation of these departments. III Water quality monitoring and preservation (i) The Project proponent shall ensure that no creeks or rivers are blocked due to any activities at the project site and free flow of water is maintained. (ii) Appropriate measures must be taken while undertaking digging activities to avoid any likely degradation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment for suspended sediment for suspended sediment efficient techniques will recue the period of impact.			
the DG sets may be decided with in consultation with State Pollution Control Board. A detailed traffic management and traffic decongestion plan shall be drawn up to ensure that the current level of service of the roads within a 05 kms radius of the project is maintained and improved upon after the implementation of the project. This plan should be based on cumulative impact of all development and increased habitation being out or proposed to be carried out by the project or other agencies in this 05 kms radius of the site in different scenarios of space and time and the traffic management plan shall be duly validated and certified by the State Urban Development department and the P.W.D./competent authority for road augmentation and shall also have their consent to the implementation of components of the plan which involve the participation of these departments. III Water quality monitoring and preservation (i) Appropriate measures must be taken while undertaking digging activities at the project site and free flow of water will maintained. (ii) Appropriate measures must be taken while undertaking digging activities to avoid any likely degradation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment of the construction techniques will recue the period of impact.			
with in consultation with State Pollution Control Board. (vii) A detailed traffic management and traffic decongestion plan shall be drawn up to ensure that the current level of service of the roads within a 05 kms radius of the project is maintained and improved upon after the implementation of the project. This plan should be based on cumulative impact of all development and increased habitation being out or proposed to be carried out by the project or other agencies in this 05 kms radius of the site in different scenarios of space and time and the traffic management plan shall be duly validated and certified by the State Urban Development department and the P.W.D./competent authority for road augmentation and shall also have their consent to the implementation of components of the plan which involve the participation of these departments. III Water quality monitoring and ensure that no creeks or rivers are blocked due to any activities at the project site and free flow of water is maintained. (ii) Appropriate measures must be taken while undertaking digging activities to avoid any likely degradation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment of suspen			
Pollution Control Board. A detailed traffic management and traffic decongestion plan shall be drawn up to ensure that the current level of service of the roads within a 05 kms radius of the project is maintained and improved upon after the implementation of the project. This plan should be based on cumulative impact of all development and increased habitation being out or proposed to be carried out by the project or other agencies in this 05 kms radius of the site in different scenarios of space and time and the traffic management plan shall be duly validated and certified by the State Urban Development department and the P.W.D./competent authority for road augmentation and shall also have their consent to the implementation of components of the plan which involve the participation of these departments. III Water quality monitoring and preservation It will be ensured that no creeks or rivers are blocked due to any activities at the project site and free flow of water is maintained. (ii) Appropriate measures must be taken while undertaking digging activities to avoid any likely degradation of water quality. Sit curtains shall be used to contain the spreading of suspended sediment of suspended sedim			
A detailed traffic management and traffic decongestion plan shall be drawn up to ensure that the current level of service of the roads within a 05 kms radius of the project is maintained and improved upon after the implementation of the project. This plan should be based on cumulative impact of all development and increased habitation being out or proposed to be carried out by the project or other agencies in this 05 kms radius of the site in different scenarios of space and time and the P.W.D./competent authority for road augmentation and shall also have their consent to the implementation of components of the plan which involve the participation of these departments. III Water quality monitoring and ensure that no creeks or rivers are blocked due to any activities at the project site and free flow of water is maintained. (ii) Appropriate measures must be taken while undertaking digging activities to avoid any likely degradation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment of the current level of service of the frame that the current level of service of the maintained and introduced in will will be ensured and in will and in win radius of the project is maintained. A detailed traffic and		with in consultation with State	
management and traffic decongestion plan shall be drawn up to ensure that the current level of service of the roads within a 05 kms radius of the project is maintained and improved upon after the implementation of the project. This plan should be based on cumulative impact of all development and increased habitation being out or proposed to be carried out by the project or other agencies in this 05 kms radius of the site in different scenarios of space and time and the traffic management plan shall be duly validated and certified by the State Urban Development department and the P.W.D./competent authority for road augmentation and shall also have their consent to the implementation of components of the plan which involve the participation of these departments. III Water quality monitoring and ensure that no creeks or rivers are blocked due to any activities at the project site and free flow of water will maintained. (ii) Appropriate measures must be taken while undertaking digging activities to avoid any likely degradation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment of service of the roads within a km radius of the purpoject is maintained. mradius of the purpoject is maintained and improved. mradius of the project is maintained and improved. mradius of the project is maintained and improved. It will be ensured that no creeks or rivers are blocked due to any activities at the project site and free flow of water will maintained. Following mitigation measures will be taken while undertaking digging activities to avoid any likely degradation of water quality. Silt curtains shall be used to contain the spreading of water than a contain the pur		Pollution Control Board.	
decongestion plan shall be drawn up to ensure that the current level of service of the roads within a 05 kms radius of the project is maintained and improved upon after the implementation of the project. This plan should be based on cumulative impact of all development and increased habitation being out or proposed to be carried out by the project or other agencies in this 05 kms radius of the site in different scenarios of space and time and the traffic management plan shall be duly validated and certified by the State Urban Development department and the P.W.D./competent authority for road augmentation and shall also have their consent to the implementation of components of the plan which involve the participation of these departments. III Water quality monitoring and preservation (i) The Project proponent shall ensure that no creeks or rivers are blocked due to any activities at the project site and free flow of water will maintained. (ii) Appropriate measures must be taken while undertaking digging activities to avoid any likely degradation of water quality. Sit curtains shall be used to contain the spreading of suspended sediment	(vii)	A detailed traffic	A detailed traffic management and traffic decongestion plan will
drawn up to ensure that the current level of service of the roads within a 05 kms radius of the project is maintained and improved upon after the implementation of the project. This plan should be based on cumulative impact of all development and increased habitation being out or proposed to be carried out by the project or other agencies in this 05 kms radius of the site in different scenarios of space and time and the traffic management plan shall be duly validated and certified by the State Urban Development department and the P.W.D./competent authority for road augmentation and shall also have their consent to the implementation of components of the plan which involve the participation of these departments. III Water quality monitoring and ensure that no creeks or rivers are blocked due to any activities at the project site and free flow of water will maintained. (ii) Appropriate measures must be taken while undertaking digging activities to avoid any likely degradation of water quality. Sit curtains shall be used to contain the spreading of suspended sediment		management and traffic	be drawn up before project comes into operation and it will be
current level of service of the roads within a 05 kms radius of the project is maintained and improved upon after the implementation of the project. This plan should be based on cumulative impact of all development and increased habitation being out or proposed to be carried out by the project or other agencies in this 05 kms radius of the site in different scenarios of space and time and the traffic management plan shall be duly validated and certified by the State Urban Development department and the P.W.D./competent authority for road augmentation and shall also have their consent to the implementation of components of the plan which involve the participation of these departments. III Water quality monitoring and ensure that no creeks or rivers are blocked due to any activities at the project site and free flow of water will maintained. III Water quality monitoring and ensure that no creeks or rivers are blocked due to any activities at the project site and free flow of water will maintained. III Water quality structure to the project site and free flow of water will maintained. III Water quality structure to the project site and free flow of water will maintained. III Water quality structure to the project site and free flow of water will maintained. III Water quality structure to the project site and free flow of water will maintained. III Water quality structure to the project site and free flow of water will maintained. III Water quality structure to the project site and free flow of water will maintained. III Water quality structure to the project site and free flow of water quality structure to encount and the project site and free flow of water quality structure to encount and the project site and free flow of water quality structure to encount and the project site and free flow of water quality structure to encount and the project site and free flow of water quality structure to encount and the project site and free flow of water quality structure to encou		decongestion plan shall be	ensured that the current level of service of the roads within a 05
roads within a 05 kms radius of the project is maintained and improved upon after the implementation of the project. This plan should be based on cumulative impact of all development and increased habitation being out or proposed to be carried out by the project or other agencies in this 05 kms radius of the site in different scenarios of space and time and the traffic management plan shall be duly validated and certified by the State Urban Development department and the P.W.D./competent authority for road augmentation and shall also have their consent to the implementation of components of the plan which involve the participation of these departments. III Water quality monitoring and preservation (i) The Project proponent shall ensure that no creeks or rivers are blocked due to any activities at the project site and free flow of water is maintained. (ii) Appropriate measures must be taken while undertaking digging activities to avoid any likely degradation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment of the project is and free flow of water quality. Silt curtains shall be used to contain the spreading of suspended sediment of the project. This plan should be based on cumulative impact of all development de		drawn up to ensure that the	km radius of the project is maintained and improved.
of the project is maintained and improved upon after the implementation of the project. This plan should be based on cumulative impact of all development and increased habitation being out or proposed to be carried out by the project or other agencies in this 05 kms radius of the site in different scenarios of space and time and the traffic management plan shall be duly validated and certified by the State Urban Development department and the P.W.D./competent authority for road augmentation and shall also have their consent to the implementation of components of the plan which involve the participation of these departments. III Water quality monitoring and preservation (i) The Project proponent shall ensure that no creeks or rivers are blocked due to any activities at the project site and free flow of water will maintained. (ii) Appropriate measures must be taken while undertaking digging activities to avoid any likely degradation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment of flower runs will be ensured. Reducing the construction time we efficient techniques will recue the period of impact.		current level of service of the	
and improved upon after the implementation of the project. This plan should be based on cumulative impact of all development and increased habitation being out or proposed to be carried out by the project or other agencies in this 05 kms radius of the site in different scenarios of space and time and the traffic management plan shall be duly validated and certified by the State Urban Development department and the P.W.D./competent authority for road augmentation and shall also have their consent to the implementation of components of the plan which involve the participation of these departments. III Water quality monitoring and preservation (i) The Project proponent shall ensure that no creeks or rivers are blocked due to any activities at the project site and free flow of water will maintained. (ii) Appropriate measures must be taken while undertaking digging activities to avoid any likely degradation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment of the plan which involve the participation of these departments. Following mitigation measures will be taken while undertaking digging activities to avoid any likely degradation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment of the plan which involve the participation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment of the plan which involve the participation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment of the plan which involve the participation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment of the plan which involve the participation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment of the project site and free flow of water will activities to avoid any likely degradation of water quality. The clean and efficient construction techniques will adopted. The construction scheduled will be strict		roads within a 05 kms radius	
and improved upon after the implementation of the project. This plan should be based on cumulative impact of all development and increased habitation being out or proposed to be carried out by the project or other agencies in this 05 kms radius of the site in different scenarios of space and time and the traffic management plan shall be duly validated and certified by the State Urban Development department and the P.W.D./competent authority for road augmentation and shall also have their consent to the implementation of components of the plan which involve the participation of these departments. III Water quality monitoring and preservation (i) The Project proponent shall ensure that no creeks or rivers are blocked due to any activities at the project site and free flow of water will maintained. (ii) Appropriate measures must be taken while undertaking digging activities to avoid any likely degradation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment of the plan which involve the participation of these departments. Following mitigation measures will be taken while undertaking digging activities to avoid any likely degradation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment of the plan which involve the participation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment of the plan which involve the participation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment of the plan which involve the participation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment of the plan which involve the participation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment of the project site and free flow of water will activities to avoid any likely degradation of water quality. The clean and efficient construction techniques will adopted. The construction scheduled will be strict		of the project is maintained	
implementation of the project. This plan should be based on cumulative impact of all development and increased habitation being out or proposed to be carried out by the project or other agencies in this 05 kms radius of the site in different scenarios of space and time and the traffic management plan shall be duly validated and certified by the State Urban Development department and the P.W.D./competent authority for road augmentation and shall also have their consent to the implementation of components of the plan which involve the participation of these departments. III Water quality monitoring and preservation (i) The Project proponent shall ensure that no creeks or rivers are blocked due to any activities at the project site and free flow of water will maintained. (ii) Appropriate measures must be taken while undertaking digging activities to avoid any likely degradation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment			
This plan should be based on cumulative impact of all development and increased habitation being out or proposed to be carried out by the project or other agencies in this 05 kms radius of the site in different scenarios of space and time and the traffic management plan shall be duly validated and certified by the State Urban Development department and the P.W.D./competent authority for road augmentation and shall also have their consent to the implementation of components of the plan which involve the participation of these departments. III Water quality monitoring and preservation (i) The Project proponent shall ensure that no creeks or rivers are blocked due to any activities at the project site and free flow of water is maintained. (ii) Appropriate measures must be taken while undertaking digging activities to avoid any likely degradation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment			
cumulative impact of all development and increased habitation being out or proposed to be carried out by the project or other agencies in this 05 kms radius of the site in different scenarios of space and time and the traffic management plan shall be duly validated and certified by the State Urban Development department and the P.W.D./competent authority for road augmentation and shall also have their consent to the implementation of components of the plan which involve the participation of these departments. III Water quality monitoring and preservation (i) The Project proponent shall ensure that no creeks or rivers are blocked due to any activities at the project site and free flow of water is maintained. (ii) Appropriate measures must be taken while undertaking digging activities to avoid any likely degradation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment			
development and increased habitation being out or proposed to be carried out by the project or other agencies in this 05 kms radius of the site in different scenarios of space and time and the traffic management plan shall be duly validated and certified by the State Urban Development department and the P.W.D./competent authority for road augmentation and shall also have their consent to the implementation of components of the plan which involve the participation of these departments. III Water quality monitoring and preservation (i) The Project proponent shall ensure that no creeks or rivers are blocked due to any activities at the project site and free flow of water is maintained. (ii) Appropriate measures must be taken while undertaking digging activities to avoid any likely degradation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment		•	
habitation being out or proposed to be carried out by the project or other agencies in this 05 kms radius of the site in different scenarios of space and time and the traffic management plan shall be duly validated and certified by the State Urban Development department and the P.W.D./competent authority for road augmentation and shall also have their consent to the implementation of components of the plan which involve the participation of these departments. III Water quality monitoring and preservation (i) The Project proponent shall ensure that no creeks or rivers are blocked due to any activities at the project site and free flow of water is maintained. (ii) Appropriate measures must be taken while undertaking digging activities to avoid any likely degradation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment		•	
proposed to be carried out by the project or other agencies in this 05 kms radius of the site in different scenarios of space and time and the traffic management plan shall be duly validated and certified by the State Urban Development department and the P.W.D./competent authority for road augmentation and shall also have their consent to the implementation of components of the plan which involve the participation of these departments. III Water quality monitoring and preservation (i) The Project proponent shall ensure that no creeks or rivers are blocked due to any activities at the project site and free flow of water is maintained. (ii) Appropriate measures must be taken while undertaking digging activities to avoid any likely degradation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment (ii) The Construction scheduled will be strictly followed and over runs will be ensured. Reducing the construction time we efficient techniques will recue the period of impact.		•	
the project or other agencies in this 05 kms radius of the site in different scenarios of space and time and the traffic management plan shall be duly validated and certified by the State Urban Development department and the P.W.D./competent authority for road augmentation and shall also have their consent to the implementation of components of the plan which involve the participation of these departments. III Water quality monitoring and preservation (i) The Project proponent shall ensure that no creeks or rivers are blocked due to any activities at the project site and free flow of water is maintained. (ii) Appropriate measures must be taken while undertaking digging activities to avoid any likely degradation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment (ii) The Project proponent shall be activities at the project site and free flow of water will activities at the project site and free flow of water will digging activities to avoid any likely degradation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment		1 3 3 3 3	
in this 05 kms radius of the site in different scenarios of space and time and the traffic management plan shall be duly validated and certified by the State Urban Development department and the P.W.D./competent authority for road augmentation and shall also have their consent to the implementation of components of the plan which involve the participation of these departments. III Water quality monitoring and preservation (i) The Project proponent shall ensure that no creeks or rivers are blocked due to any activities at the project site and free flow of water is maintained. (ii) Appropriate measures must be taken while undertaking digging activities to avoid any likely degradation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment			
site in different scenarios of space and time and the traffic management plan shall be duly validated and certified by the State Urban Development department and the P.W.D./competent authority for road augmentation and shall also have their consent to the implementation of components of the plan which involve the participation of these departments. III Water quality monitoring and preservation (i) The Project proponent shall ensure that no creeks or rivers are blocked due to any activities at the project site and free flow of water is maintained. (ii) Appropriate measures must be taken while undertaking digging activities to avoid any likely degradation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment			
space and time and the traffic management plan shall be duly validated and certified by the State Urban Development department and the P.W.D./competent authority for road augmentation and shall also have their consent to the implementation of components of the plan which involve the participation of these departments. III Water quality monitoring and preservation			
management plan shall be duly validated and certified by the State Urban Development department and the P.W.D./competent authority for road augmentation and shall also have their consent to the implementation of components of the plan which involve the participation of these departments. III Water quality monitoring and preservation			
duly validated and certified by the State Urban Development department and the P.W.D./competent authority for road augmentation and shall also have their consent to the implementation of components of the plan which involve the participation of these departments. III Water quality monitoring and preservation (i) The Project proponent shall ensure that no creeks or rivers are blocked due to any activities at the project site and free flow of water is maintained. (ii) Appropriate measures must be taken while undertaking digging activities to avoid any likely degradation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment (iii) Appropriate measures must be taken while undertaking digging activities to avoid any likely degradation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment		-	
the State Urban Development department and the P.W.D./competent authority for road augmentation and shall also have their consent to the implementation of components of the plan which involve the participation of these departments. III Water quality monitoring and preservation (i) The Project proponent shall ensure that no creeks or rivers are blocked due to any activities at the project site and free flow of water is maintained. (ii) Appropriate measures must be taken while undertaking digging activities to avoid any likely degradation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment			
department and the P.W.D./competent authority for road augmentation and shall also have their consent to the implementation of components of the plan which involve the participation of these departments. III Water quality monitoring and preservation			
P.W.D./competent authority for road augmentation and shall also have their consent to the implementation of components of the plan which involve the participation of these departments. III Water quality monitoring and preservation (i) The Project proponent shall ensure that no creeks or rivers are blocked due to any activities at the project site and free flow of water will maintained. (ii) Appropriate measures must be taken while undertaking digging activities to avoid any likely degradation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment P.W.D./competent authority for road augmentation and shall also have their consent to the implementation of components of the plan which involve the participation of these departments. It will be ensured that no creeks or rivers are blocked due to a activities at the project site and free flow of water will maintained. Following mitigation measures will be taken while undertaking digging activities to avoid any likely degradation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment		-	
for road augmentation and shall also have their consent to the implementation of components of the plan which involve the participation of these departments. III Water quality monitoring and preservation (i) The Project proponent shall ensure that no creeks or rivers are blocked due to any activities at the project site and free flow of water is maintained. (ii) Appropriate measures must be taken while undertaking digging activities to avoid any likely degradation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment for road augmentation and shall be involved to the implementation of components of the plan which involve the participation of these departments. It will be ensured that no creeks or rivers are blocked due to a activities at the project site and free flow of water will maintained. Following mitigation measures will be taken while undertaking digging activities to avoid any likely degradation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment			
shall also have their consent to the implementation of components of the plan which involve the participation of these departments. III Water quality monitoring and preservation (i) The Project proponent shall ensure that no creeks or rivers are blocked due to any activities at the project site and free flow of water is maintained. (ii) Appropriate measures must be taken while undertaking digging activities to avoid any likely degradation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment shall also have their consent to the implementation of components of the plan which involve the participation of these departments. It will be ensured that no creeks or rivers are blocked due to a activities at the project site and free flow of water will maintained. Following mitigation measures will be taken while undertaking digging activities to avoid any likely degradation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment			
to the implementation of components of the plan which involve the participation of these departments. III Water quality monitoring and preservation (i) The Project proponent shall ensure that no creeks or rivers are blocked due to any activities at the project site and free flow of water is maintained. (ii) Appropriate measures must be taken while undertaking digging activities to avoid any likely degradation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment			
components of the plan which involve the participation of these departments. III Water quality monitoring and preservation (i) The Project proponent shall ensure that no creeks or rivers are blocked due to any activities at the project site and free flow of water is maintained. (ii) Appropriate measures must be taken while undertaking digging activities to avoid any likely degradation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment Components of the plan which involve the participation of these departments. III Water quality monitoring and preservation			
involve the participation of these departments. III Water quality monitoring and preservation (i) The Project proponent shall ensure that no creeks or rivers are blocked due to any activities at the project site and free flow of water is maintained. (ii) Appropriate measures must be taken while undertaking digging activities to avoid any likely degradation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment involve the participation of preservation It will be ensured that no creeks or rivers are blocked due to a activities at the project site and free flow of water will maintained. Following mitigation measures will be taken while undertaking digging activities to avoid any likely degradation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment			
these departments. III Water quality monitoring and preservation (i) The Project proponent shall ensure that no creeks or rivers are blocked due to any activities at the project site and free flow of water is maintained. (ii) Appropriate measures must be taken while undertaking digging activities to avoid any likely degradation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment (iii) Water quality monitoring and preservation It will be ensured that no creeks or rivers are blocked due to a activities at the project site and free flow of water will maintained. Following mitigation measures will be taken while undertaking digging activities to avoid any likely degradation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment			
III Water quality monitoring and preservation			
(ii) The Project proponent shall ensure that no creeks or rivers are blocked due to any activities at the project site and free flow of water is maintained. (ii) Appropriate measures must be taken while undertaking digging activities to avoid any likely degradation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment (iii) The Project proponent shall be will be ensured that no creeks or rivers are blocked due to a activities at the project site and free flow of water will maintained. Following mitigation measures will be taken while undertaking digging activities to avoid any likely degradation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment	111	·	Inreservation
ensure that no creeks or rivers are blocked due to any activities at the project site and free flow of water is maintained. (ii) Appropriate measures must be taken while undertaking digging activities to avoid any likely degradation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment activities at the project site and free flow of water will maintained. Following mitigation measures will be taken while undertaking digging activities to avoid any likely degradation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment			
rivers are blocked due to any activities at the project site and free flow of water is maintained. (ii) Appropriate measures must be taken while undertaking digging activities to avoid any likely degradation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment maintained. Following mitigation measures will be taken while undertaking digging activities to avoid any likely degradation of water adopted. The clean and efficient construction techniques will adopted. The construction scheduled will be strictly followed and over runs will be ensured. Reducing the construction time we efficient techniques will recue the period of impact.	(1)	, , ,	•
activities at the project site and free flow of water is maintained. (ii) Appropriate measures must be taken while undertaking digging activities to avoid any likely degradation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment Appropriate measures must digging activities to avoid any likely degradation of water quality. The clean and efficient construction techniques will adopted. The construction scheduled will be strictly followed and over runs will be ensured. Reducing the construction time we efficient techniques will recue the period of impact.			
and free flow of water is maintained. (ii) Appropriate measures must be taken while undertaking digging activities to avoid any likely degradation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment Following mitigation measures will be taken while undertaking digging activities to avoid any likely degradation of water quality. The clean and efficient construction techniques will adopted. The construction scheduled will be strictly followed and over runs will be ensured. Reducing the construction time we efficient techniques will recue the period of impact.		-	mamameu.
(ii) Appropriate measures must be taken while undertaking digging activities to avoid any likely degradation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment Following mitigation measures will be taken while undertaking digging activities to avoid any likely degradation of water adopted. • The clean and efficient construction techniques will adopted. • The construction scheduled will be strictly followed and over runs will be ensured. Reducing the construction time we efficient techniques will recue the period of impact.			
 (ii) Appropriate measures must be taken while undertaking digging activities to avoid any likely degradation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment Following mitigation measures will be taken while undertaking digging activities to avoid any likely degradation of water quality. The clean and efficient construction techniques will adopted. The construction scheduled will be strictly followed and over runs will be ensured. Reducing the construction time we efficient techniques will recue the period of impact. 			
be taken while undertaking digging activities to avoid any likely degradation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment digging activities to avoid any likely degradation of water quality. The clean and efficient construction techniques will adopted. The construction scheduled will be strictly followed and over runs will be ensured. Reducing the construction time we efficient techniques will recue the period of impact.	(")		Falls to a straight and a second state of the state of th
 digging activities to avoid any likely degradation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment The clean and efficient construction techniques will adopted. The construction scheduled will be strictly followed and over runs will be ensured. Reducing the construction time we efficient techniques will recue the period of impact. 	(ii)		
likely degradation of water quality. Silt curtains shall be used to contain the spreading of suspended sediment adopted. • The construction scheduled will be strictly followed and over runs will be ensured. Reducing the construction time we efficient techniques will recue the period of impact.			
quality. Silt curtains shall be used to contain the spreading of suspended sediment • The construction scheduled will be strictly followed and over runs will be ensured. Reducing the construction time we efficient techniques will recue the period of impact.		, ,,	·
used to contain the spreading over runs will be ensured. Reducing the construction time w efficient techniques will recue the period of impact.			•
of suspended sediment efficient techniques will recue the period of impact.			The construction scheduled will be strictly followed and no
of suspended sediment efficient techniques will recue the period of impact.			over runs will be ensured. Reducing the construction time with
		•	
		during dredging within the	The scrap and waste construction materials will not be
dredging area. disposed into the seawater.		dredging area.	
		of suspended sediment during dredging within the	efficient techniques will recue the period of impact.The scrap and waste construction materials will not be

		 As proposed, dredging material will be utilized for raising the Ground Level of 39 Ha plot to match with the existing Ground Level and balance material and maintenance dedge spoil will be disposed at the GMB designated dredged spoil disposal locations.
(iii)	No ships docking at the proposed project site will discharge its on-board wastewater untreated into the estuary/channel. All such wastewater load will be diverted to the proposed	We will be implementing and adhering to "SHIP SHORE Safety Checklist Protocol" for every Ship and will be attested by both GCPTCL (Loading Master) and Ship (Chief Officer). Disposal of garbage/air pollution will not be allowed at Jetty/anchorage which will be acknowledged and followed by the Chief Officer of the Ship.
	Effluent Treatment Plant of the Project site.	Vessels visiting the berths will not be allowed to release/discharge oily waste, ballast & solid waste including wastes in marine environment and the same will be ensured through implementation of "Indemnity Letter and Condition of Use of GCPTC Jetty".
(iv)	Measures should be taken to contain, control and recover the accidental spill of fuel and cargo handle.	Following specific efforts / best practices / RAGAGEP will be in place to ensure elimination/minimize spillage of hazardous chemicals during its storage and handling.
	3	 Handling of products through closed systems – use of piping and loading arms for transfer/handling of products Flange joints in the piping network will be of full faced gasket joint and valves (stem) equipped with graphite fitting etc.
		Material transfer pumps will be of centrifugal type and will be provided with double mechanical seals.
		 Close drain system (OWS/PWS) – independent of domestic waste and storm water drainage will be provided across the Terminal area including gantry operation facility.
		COMPLIED.
(v)	The project proponents will draw up and implement a plan for the management of temperature differences between intake waters and discharge waters.	As there are no production activities associated with the project, there will not be any requirement to install intake and discharge facilities.
(vi)	Spillage of fuel/engine oil and lubricants from the construction site are a source of organic pollution which	Provision of nets, barricading etc. will be ensured during the construction phase in area for transfer of material to avoid spillage of material in intertidal and sub tidal areas.
	impacts marine life. This shall be prevented by suitable precautions and also by providing necessary	Piling and service platform are the two key structural activities of Jetty establishment (i.e. making provision of mooring dolphins and loading arm).
	mechanisms to trap the spillage.	For the purpose, we will consider and adopt state of the art technology like ready to use steel piles imported via sea route and pre-caste slabs with due consideration to eliminating/minimizing likelihood of environment impact.
(vii)	Total fresh water use shall not exceed the proposed requirement as provided in	There will be no increase in the existing water consumption, domestic wastewater generation and industrial effluent generation from the consented quantities.

project details. Prior Details of water consumption during the last 3 years appended permission from the as below for ready reference competent authority shall be obtained for use of fresh 2019-20 Year 2018-19 2020-21 water. Allocated water supply 1590 1590 1590 by GIDC KLD **Average** consumption 512 651 775 of water in KLD Water consumption during October 2020 to March 2021 is 779 KLD. Details of wastewater generated during the last 3 years is appended as below for ready reference -Consented Quantity Generation in KL in **KLD** Year 2018-19 2019-20 2020-21 125 Industrial 2.8 2.7 11.6 40 35.43 36.80 Domestic 36.33 **Consented Quantity** Generation in KL in KLD Year 2020-21 (October 2020 to March 2021) Industrial 125 6.9 Domestic 40 39.2 COMPLIED. (viii) Treatment Plant Sewage Treatment Plant with adequate capacity will be installed Sewage to treat domestic wastewater generated from chemical storage shall be provided to treat the wastewater generated from area and jetty area. Treated water will be utilized in Horticulture the project. Treated water purpose. shall be reused for horticulture. flushing, backwash, HVAC purposes and dust suppression. (ix) certificate from the Treated water from the Effluent Treatment Plan will be utilized for competent authority for Horticulture purpose within the plant area. There will not be any discharging treated discharge of treated effluent/untreated effluents into the Public effluent/untreated effluents sewer/disposal/drainage systems. into the **Public** sewer/disposal/drainage systems along with the final disposal point should be obtained.

(x) No diversion of the natural No diversion of the natural courses of the river will be required. courses of the river shall be prior made without permission from the Ministry of Waste resources. (xi) ΑII the erosion control Following erosion control measures will be taken at water front measures shall be taken at water front facilities. Earth Proper spacing between the piles will be provided so that the protection work shall be pile structures will not impact the free flow of the water, wave carried out to avoid erosion of activity and the seabed sediment movement. Therefore, there soil from the will not be any shoreline erosion. shoreline/boundary line from There will not be any construction bund across the intertidal the land area into the marine zone. water body. Construction waste and debris will not be left in intertidal zone or nearshore. Noise monitoring and prevention IV Noise level survey shall be (i) Practice is in place for monitoring of Noise level, at periodic level, carried as per the prescribed within the complex at workplace as well as at the extreme guidelines and report in this perimeter through MoEF&CC and NABL recognized third party regard shall be submitted to as well as by internal resource and records are maintained Regional Office of the (Annexure-C). Ministry as a part of sixmonthly compliance report. Summary of Ambient and Workplace noise level monitoring from (October 2020 to March 2021) is presented as below for ready reference. Area/Location **Average** Minimum Maximum Ambient Air Noise Monitoring - DAY/NIGHT in dB(A) Nearby Store 56/52 52/47 66/62 Main Gate 58/53 54/49 62/59 Material Gate 59/55 56/47 64/62 Landfall Point 57/54 49/47 66/59 At Workplace Noise Monitoring – in dB(A) Jetty Service Platform 55/52 48/46 62/53 BOG Compressor House 62/57 59/48 66/60 Mechanical Workshop 48/46 62/58 55/51 Gantry Area 56/52 48/46 60/55 From the above details, it is confirmed that the overall noise level is within the limit prescribed in EPA, 1986. COMPLIED. Noise from vehicles, power Standard Maintenance Practices (SMP) will be in place for (ii) machinery and equipment onconducting Preventive Maintenance (PM) of machinery like site should not exceed the pumps, compressors, blowers etc. includes prescribed limit. Equipment lubrication/alignment/abnormal noise etc. PM requirement will be should be regularly serviced. integrated in SAP. Attention should also be given to muffler maintenance and enclosure of noisy

equiments.

(iii)	Acoustic enclosures for DG sets, noise barriers for ground-run bays, ear plugs for operating personnel shall be implemented as mitigation measures for noise impact due to ground sources.	Noise suppression measurapplicable like pumps will provision of an enclosure e Ear defenders, plugs, memployees/workers engage area. Acoustic enclosure for DG sign FIA/FAMP are not to the suppression measure.	be provided tc. uffs will be ed in carrying	with muffler provided to out activity in	on exhaust, o company n high noise
(iv)	The ambient noise level should conform to the standards prescribed under E(P)A Rules, 1986 viz. 75 dB(A) during day time and 70 dB(A) during night time.	in EIA/EMP report. Practice is in place for moni within the complex at wo perimeter through MoEF&C as well as by internal res (Annexure-C). Summary of Ambient and V (October 2020 to March 20 reference.	orkplace as CC and NAB source and	well as at t BL recognized records are sise level mon	the extreme d third party maintained nitoring from
		Area/Location	Average	Minimum	Maximum
		Ambient Air Noise Moni	toring - DA	Y/NIGHT in o	B(A)
		Nearby Store	56/52	52/47	66/62
		Main Gate	58/53	54/49	62/59
		Material Gate	59/55	56/47	64/62
		Landfall Point	57/54	49/47	66/59
		From the above details, it is is within the limit prescribed			ll noise level
		COMPLIED.			
V	Energy Conservation Measur	res			
(i)	Provide solar power generation on roof tops of buildings, for solar light system for all common areas, street lights, parking around project area and maintain the same regularly.	Solar power generation faci and will be maintained regu	ılarly.		
(ii)	Provide LED lights in the offices and project areas.	LED lights will be provided	in the offices	and project	areas.
VI	Waste Management				
(i)	Dredged material shall be disposed safely in the designated areas.	Dredging work for the expandance However, as proposed the raising the ground level of the surplus dredge material site.	e dredged n 39 Ha. diver	naterial will ted plot and/	be used for or disposing
(ii)	Shoreline should not be disturbed due to dumping. Periodical study on shore line changes shall be conducted and mitigation carried out, if necessary. The details shall be submitted along with the	Noted.			

	six monthly monitoring reports.	
(iii)	Necessary arrangements for the treatment of the effluents and solid wastes must be made and it must be ensured that they conform to the standards laid down by the competent authorities including the Central or State Pollution Control Board and under the Environment (Protection) Act, 1986.	Major part of wastewater generation will be sewage and considerable quantity of trade effluent, which will be possible only during non-routine activities like cleaning of tanks, which will be possible once in blue moon as chemical specific independent storage tanks will be built. In such cases, the effluent generated will be taken to ETP for treatment and disposal. Septic tanks/soak pit systems will be provided for disposal of sewage. Very insignificant quality of trade effluent titled as cooling tower blow down will be generated as routine and will be used on land for green belt development as its quality confirms to the prescribed limit.
(iv)	The solid waste shall be managed and disposed as per the norms of the Solid Waste Management Rules, 2016.	Solid waste generated at site will be disposed as per the provisions of the Solid Waste Management Rules, 2016.
(v)	Any wastes from construction and demolition activities related thereto shall be managed so as to strictly conform to the Construction and Demolition Rules, 2016.	Any wastes from construction and demolition activities related thereto will be managed as per the Construction and Demolition Rules, 2016.
(vi)	A certificate from the competent authority handling municipal solid wastes should be obtained, indicating the existing civic capacities of handling and their adequacy to cater to the M.S.W. generated from the project.	A certificate of the competent authority handling Municipal Solid Waste will be obtained prior to construction activities for the expansion project start.
(vii)	Used CFLs and TFLs should be properly collected and disposed off/sent for recycling as per the prevailing guidelines/ rules of the regulatory authority to avoid mercury contamination.	Used CFLs and TFLs will be collected properly and will be disposed off/sent for recycling as per the prevailing guidelines/rules of the GPCB to avoid mercury contamination.
(viii)	Oil spill contingency plan shall be prepared and part of the DMP to tackle emergencies. The equipment and recovery of oil from a spill would be assessed. Guidelines given in MARPOL and Shipping Acts for oil spill management would be followed. Mechanism for integration of terminals oil contingency plan with the overall area contingency plan	We have prepared Oil spill contingency plan and submitted for approval vide our letter dated 14.10.2017. Approval for the same is still pending. Copy of the same is attached herewith as an Annexure-D.

	under the co-ordination of	
	Coast should be covered.	
VII	Green Belt	
(i)	Green belt shall be developed in area as provided in project details with a native tree species in accordance with CPCB guidelines.	The terminal has developed and maintained green belt as mentioned below; • Greenbelt width of 100 meters in the periphery of the company having density of ~ 1000 trees/Acre • Total green belt area : 35 Hectors • Total no. of trees : 87500
		Green belt has been developed using native plant species (Azadiractaindica, Peltophorumindica, Kejurina, Bahomiapurpuria, ficusreligiosa, Ficusbenghalensis, TerminaliaArjuna etc.) of plants and is being maintained.
		Water sprinkling and drip irrigation system are being used for the green belt development / horticulture purpose.
		Sprinkling System System Erigation
		Approximately 35 Ha. Green belt/Green cover has been developed within the premises.
		 All the topsoil approx. 455 tractors had already been utilized in green belt/ landscape development In Addition to this, saplings continue along the roadside boundary/open space available outside the company premises as well as in the neighboring villages in consultation with GIDC, Dahej during 2018-19, 2019-20 and 2020-21.
		COMPLIED.
(ii)	Top soil shall be separately stored and used in the	Top soil will be stored separately and will be utilized in the greenbelt development.
VIII	development of green belt. Marine Ecology	
(i)	Dredging shall not be carried out during the fish breeding	Noted.
<u> </u>	and spawning seasons.	

(ii)	Dredging, etc. shall be carried	Noted and agreed.
	out in the confined manner to	
	reduce the impacts on marine	
	environment.	
(iii)	The dredging schedule shall	Dredging schedule will be so planned that turbidity developed is
	be so planned that turbidity	dispersed soon enough to prevent any stress on the fish
	developed is dispersed soon	population.
	enough to prevent any stress	
	on the fish population.	
(iv)	While carrying out dredging,	Noted.
	an independent monitoring	
	shall be carried out through a	
	Government Agency/Institute	
	to assess the impact and	
	necessary measures shall be	
	taken on priority basis if any	
	adverse impact is observed.	
(v)	A detailed marine biodiversity	Construction activities of the expansion project has not been
	management plan shall be	started yet. However, a detailed marine biodiversity management
	prepared through the NIO or	plan will be prepared through the NIO or any other institute of
	any other institute of repute	repute on marine, brackish water and fresh water ecology and
	on marine, brackish water	biodiversity. Marine Environmental Monitoring will be carried out
	and fresh water ecology and	through competent agencies during construction and operation
	biodiversity and submitted to	phase of the expansion project and reports will be submitted to
	and implemented to the	Gujarat Biodiversity Board and the CRZ Authority.
	satisfaction of the State	
	Biodiversity Board and the	
	CRZ authority. The report	
	shall be based on a study of	
	the impact of the project	
	activities on the intertidal	
	biotopes, corals and coral	
	communities, molluscs, sea	
	grasses, sea weeds, sub-tidal	
	habitats, fishes, other marine	
	and aquatic micro, macro and	
	mega flora and fauna	
	including benthos, plankton,	
	turtles, birds, etc. as also the	
	productivity. The data	
	collection and impact	
	assessment shall be as per	
	standards survey methods	
	and include underwater	
	photography.	
(vi)	Marine ecology shall be	Marine ecology will be monitored during construction, post
	monitored regularly also in	construction and operation phase in terms of sea weeds, sea
	terms of sea weeds, sea	grasses, mudflats, sand dunes, fisheries, echinoderms, shrimps,
	grasses, mudflats, sand	turtles, corals, coastal vegetation, mangroves and other marine
	dunes, fisheries,	biodiversity components including all micro; macro and mega
	echinoderms, shrimps,	floral and faunal components of marine biodiversity.
	turtles, corals, coastal	
	vegetation, mangroves and	
	other marine biodiversity	
	components including all	
	micro, macro and mega floral	

	and faunal components of marine biodiversity.				
(vii)	The project proponent shall ensure that water traffic does not impact the aquatic wildlife sanctuaries that fall along the stretch of the river.	It will be ensured the wildlife sanctuaries			
IV	Dublic heaving and houses he				
(i) The work space shall be maintained as per the international standards for occupational health and safety provisions of fresh air respirators, blowers and fans to prevent any accumulation and inhalation of undesirable levels of pollutants including VOCs.		The work place is being maintained as per the international standards for occupational health and safety provisions of fresh air respirators, blowers and fans to prevent any accumulation and inhalation of undesirable levels of pollutants including VOCs. Workplace monitoring for presence of hazardous chemicals, if any is carried out through MoEF&CC and NABL accredited laboratory M/s. Kadam Environmental Consultants, Vadodara. Summary of monitoring of hazardous chemical at workplace for the reporting period i.e., (October 2020 to March 2021) is appended as below for ready reference.			
		Hazardous	Average	Minimum	Maximum
		chemical	mgm3	mg/m3	mg/m3
		Px	3.59	2.37	5.38
		Methanol	3.12	1.61	6.12
		Hydrocarbon	2.27	1.24	3.11
		Butadiene	ND	ND	ND
		Acetic Acid	ND	ND	ND
		Caustic Fumes	ND	ND	ND
		Propylene Oxide	ND	ND	ND
		Propane	3.96	2.68	6.68
(ii)	Workers shall be strictly enforced to wear personal	Report of one such is attached herewith Personal protective gloves, goggles, ea	as an Annexu equipments like	e helmet, safety	shoes, hand
	protective equipments like dust mask, ear muffs or ear plugs, whenever and wherever necessary/required. Special visco-elastic gloves will be used by labour exposed to hazards from vibration.				
(iii)	In case of repair of any old vessels, excessive care shall be taken while handling Asbestos & Freon gas. Besides, fully enclosed covering should be provided for the temporary storage of	No vessels repairing	g activities will b	e carried out.	

	asbestos materials at site before disposal to CTSDF.			
(iv)	Safety training shall be given to all workers specific to their work area and every worker and employee will be engaged in fire hazard awareness training and mock drills which will be conducted regularly. All standard safety and occupational hazard measures shall be implemented and monitored by the concerned officials to prevent the occurrence of untoward incidents/accidents.	work area and every wo hazard awareness tra conducted regularly. All	aining and mock drill standard safety and oc mented and monitored	be engaged in fire s which will be cupational hazard
(v)	Emergency preparedness plan based on the Hazard Identification and Risk Assessment (HIRA) and Disaster Management Plan shall be implemented.	Construction activities for been started yet. However, on the hazard identificing disaster management prior to construction activities.	ver, emergency prepare cation and risk assessi plan will be prepared	dness plan based ment (HIRA) and
(vi)	Provision shall be made for the housing of construction labour within the site with all necessary infrastructure and facilities such as fuel for cooking, mobile toilets, mobile STP, safe drinking water, medical health care, crèche etc. The housing may be in the form of temporary structures to be removed from after the completion of the project.	Providing construction and facilities such as dri sewage plant) etc. will and such camps will not and were located outsid Workers engaged preferred/opted from ne	inking water, sanitation (be direct responsibility the allowed within the code.	(mobile toilets and of the contractor ompany premises tivities will be
(vii)	Occupational health surveillance of the workers shall be done on a regular basis.	Examination) → At every six month process (i.e. Period	PTCL and is carried or pries Act and Gujarat Fraintained in OHC. Urveillance is carried outing formality (i.e. Pre-Emas for all workers engaging Fitness Examination) ucted at the time of Fitness	is one of the on- ut at a frequency factory Rules and t – nployment Fitness ged in hazardous
		Fitness Examination Parameter Physician Check-up Eye – Check-up	Pre-Employment Fitness Examination	Periodic Fitness Examination

ENT- Check-up	V	V
X-ray	V	V
ECG	V	V
Urine Routine	V	V
CBC+ESR	V	V
Blood Group	V	V
Random Blood	2	2
Sugar	V	V

Typical sample lab analysis reports of Pre-Employment as well as Periodical Fitness Examination for company employee and contractors are attached as **Annexure 63 and Annexure 64** respectively.

Records of such fitness examination are maintained in a standard template as prescribed in the Factories Act and the Gujarat Factories Rules i.e. in Form No 33 (Pre-Employment) Form No 32 (Periodical).

Typical example of one such record is appended as below for ready reference."

CERTIFIC	ATE OF FITNESS OF EMPLOYM	der Rule-68- T and 102) ENT IN HAZARDOUS PROCESS AND (E FACTORY MEDICAL OFFICER)	OPERATIONS
1. Employee Code N	o. :		
2. Name of the Pers	on Examined : 96	EPAK TUKARAM GHACH	0645
3. Father's Name			gene
4. Sex	:_ ~	ele	
5. Residence		Suret)/GEPTCL.	
G. Date of Birth, if a		09-11-1766	
7. Name & Address o		CPL.	
B. The worker is Emp		•	
a. Hazardous Pro	ocess :	_	
b. Dangerous Op	peration :	_	
Leartify that	I have personally average of the	above named person whose identific	
mode on	neok.	and who is desirous	ation marks are
n my opinion he / sho n my opinion he / sho eason urther exmination to	e is unfit for employment in the the certifying surgeon	id manufacturing process / operation said manufacturing process / operat	
n my opinion he / sh n my opinion he / sh pason urther exmination to the serial number of the Signature of	e is fit for employment in the sa e is unfit for employment in the the certifying surgeon the previous certificate is	Id manufacturing process / operation said manufacturing process / operation He / she is He / she is Signature of Factory Radical Conference of Factory Radic	on for the referred for
n my opinion he / sh n my opinion he / sh pason urther exmination to the serial number of the Signature of	e is fit for employment in the sa e is unfit for employment in the the certifying surgeon the previous certificate is the previous certificate is the previous certificate is the previous certificate is	id manufacturing process / operation said manufacturing process / operat He / she is Signature of Factory Modical Factory Mod	ion for the referred for Differs 3.5.5.5.5.1.H. G-34771
n my opinion he / sh n my opinion he / sh eason urther exmination to he serial number of Signature o Impression of th	e is fit for employment in the sa e is unfit for employment in the the certifying surgeon the previous certificate is open in the previous certificate is open in the previous certificate is open in the previous certificate is open in the previous	id manufacturing process / operation said manufacturing process / operat He / she is He / she is Signature of Factory Medical of She is shown of Factory cal Officer with of the Factory Factory Medi	ion for the referred for Differs 3.5.5.5.5.1.H. G-34771
n my opinion he / sh n my opinion he / sh pason urther exmination to the serial number of the Signature of	e is fit for employment in the sa e is unfit for employment in the the certifying surgeon the previous certificate is ight hand thumb e person examined	di manufacturing process / operation said manufacturing process / operation He / she is Signature of Factory Medical of Here with of the Factory Medical of Signs and symbols observed	ion for the referred for Differs 3.5.5.5.5.1.H. G-34771
n my opinion he / sh n my opinion he serial number of he serial number of light serial number of ligh	e is fit for employment in the sa e is unfit for employment in the the certifying surgeon the previous certificate is compared to the previous certificate is compared to the previous certificate is compared to the person examined surgeon to the person examined to person examined the person examined to the person examined to person examined to the person examined t	Signature of Factory Modical Or North Market Williams of Factory Modification of Market Williams of Market Wi	officer sava
n my opinion he / sh n my opinion he my opinion he serial number of Signature or impression of the learning the person nentioned above on date of examination)	e is fit for employment in the sa e is unfit for employment in the the certifying surgeon the previous certificate is compared to the previous certificate is compared to the previous certificate is compared to the person examined surgeon to the person examined to person examined the person examined to the person examined to person examined to the person examined t	sid manufacturing process / operation said manufacturing process / operation He / she is He / she is Signature of Factory Andicion Lamp of Factory said Officer with Orther Factory Factory Medi Signs and symtoms observed doing examination Weight : / 70 cm Weight : / 70 cm Weight : / 70 fm BP ! ! ! / 10 fm m of fg ! ! ! ! / 10 fm m of fg ! ! ! ! / 10 fm m of fg ! ! ! ! / 10 fm m of fg ! ! ! ! / 10 fm m of fg ! ! ! ! / 10 fm m of fg ! ! ! ! / 10 fm m of fg ! ! ! ! / 10 fm m of fg ! ! ! ! / 10 fm m of fg ! ! ! ! ! / 10 fm m of fg ! ! ! ! ! 10 fm m of fg ! ! ! ! 10 fm m of fg ! ! ! ! 10 fm m of fg ! ! ! ! 10 fm m of fg ! ! ! ! 10 fm m of fg ! ! ! ! 10 fm m of fg ! ! ! ! 10 fm m of fg ! ! ! ! 10 fm m of fg ! ! ! ! 10 fm m of fg ! ! ! ! 10 fm m of fg ! ! ! ! 10 fm m of fg ! ! ! ! 10 fm m of fg ! ! ! ! 10 fm m of fg ! ! ! ! 10 fm m of fg ! ! ! ! 10 fm m of fg ! ! ! ! ! ! 10 fm m of fg ! ! ! ! ! ! ! 10 fm m of fg ! ! ! ! ! ! ! ! ! ! ! ! ! ! ! ! ! ! !	Officersava 3. V., C.I.H. G34771 Cal Officer Signature of the Factory Medical

COMPLIED.

X Environment Responsibility

The company shall have a well laid down environmental policy duly approved by the Board of Directors. The environmental policy should prescribe for standard operating procedures to have proper checks and balances and to bring into focus any infringements/deviations/viol ation of the environmental/forest/wildlife

Environmental policy duly signed by Managing Director of the company had been laid down. Copy of the same is attached herewith as an **Annexure-E**.

(ii)	The copy of the board resolution in this regard shall be submitted to the MoEF&CC as a part of sixmonthly report. A separate Environmental Cell both at the project and company head quarter level, with qualified personnel shall be set up under the control of senior Executive, who will directly report to the head of the organization.	A separate environment management cell headed by Head – HSEF and supported by an Environment Manager / HSE Manager having M. Tech. (Environmental Science and Engineering) qualification. Detailed organogram of HSEF department as on date is appended as below for ready reference. GUJARAT CHEMICAL PORT TERMINAL COMPANY LIMITED ORGANIZATIONAL CHART - HSEF Department MANAGING DIRECTOR Executive Director Head of Operation Head HSEF (1) Manager HSEF (1) Assistant Mgr HSEF (4) Supervisor (1) Fire Pump Operator (3) Fire Pump Operator (3)
		Existing lab of promoter company M/s RIL (Dahej Manufacturing Division) is being utilized as Environmental Laboratory to monitor/analyze basic parameters of the Water Quality. Apart from this, environmental monitoring is being carried out at regular interval through MoEF&CC recognized and NABL accredited laboratory. COMPLIED.
(iii)	Action plan for implementing EMP and environmental conditions along with responsibility matrix of the company shall be prepared	Budgeting for Environment protection measures and CSR including socio-economic constitutes a part of overall budget plan and sufficient funds are earmarked every year for environmental management program including monitoring and analysis.

	1	
	and shall be duly approved by competent authority. The year wise funds earmarked for environmental protection	Environment Budget: 2020 – 21 SN Item INR - Lakh 1 Environment monitoring & Hazardous waste management 13.45
	measures shall be kept in	2 Oil spill response 54.69
	separate account and not to	3 Green belt/horticulture 19.00
	be diverted for any other	4 Housekeeping 19
	purpose. Year wise progress	3
	of implementation of action	Total - Lakhs 107.14
	plan shall be reported to the	
	Ministry/Regional Office	
	along with the Six Monthly Compliance Report.	Note: Budget Under the Activities Listed as above may subject to change based on inputs / discussion/ issues shortlisted/ identified/ presented during the Public Hearing.
(:)	Out of the last	COMPLIED.
(iv)	Self environmental audit shall	Noted.
	be conducted annually. Every	
	three years third party	
	environmental audit shall be	
VI	carried out.	
XI (i)	Miscellaneous The project propensat shall	The news regarding grant of Environmental Clearance was
(i)	The project proponent shall make public the	published in two local newspapers namely Divya Bhaskar (in
	environmental clearance	Gujarati Language) dated 25.12.2020 & Times of India Baroda
	granted for their project along	Edition (in English Language) dated 25.12.2020.
	with the environmental	Conv. of the same is attached haravith as Anneyure E.1.9
	conditions and safeguards at	Copy of the same is attached herewith as Annexure F-1 &
	their cost by prominently	Annexure F-2.
	advertising it at least in two	
	local newspapers of the	
	District or State, of which one	
	shall be in the vernacular	
	language within seven days	
	and in addition this shall also	
	be displayed in the project	
	proponent's website	
	permanently.	
(ii)	The copies of the	Intimation had been submitted to the panchayat of village
1	environmental clearance	Lakhigam, Taluka Vagra, District Bharuch vide our letter dated
	shall be submitted by the	24.12.2020. Copy of the same is attached herewith as an
	project proponents to the	Annexure G.
	Heads of the local bodies,	
	Panchayats and Municipal	
	Bodies in addition to the	
	relevant offices of the	
	Government who in turn has	
	to display the same for 30	
	days from the date of receipt.	
(iii)	The project proponent shall	Noted.
` '	upload the status of	
	compliance of the stipulated	
1	environment clearance	
	conditions, including results	
	of monitored data on their	
L	or monitored data on their	

	website and update the same	
	on half-yearly basis.	
(iv)	The project proponent shall submit six-monthly reports on the status of the compliance of the stipulated environmental conditions on the website of the ministry of Environment, Forest and Climate Change at environment clearance portal.	Six monthly reports on the status of the compliance of the stipulated environmental conditions are being submitted on the website of the ministry of Environment, Forest and Climate Change. Last Six monthly reports on the status of the compliance of the stipulated environmental conditions was submitted to Ministry on 25.01.2021.
(v)	The project proponent shall submit the environmental statement for each financial year in Form-V to the concerned State Pollution Control Board as prescribed under the Environmental (Protection) Rules, 1986, as amended subsequently and put on the website of the company.	The Environmental Statement of each financial year in Form-V is being submitted to the Gujarat Pollution Control Board. Form-V of last financial year (i.e. 2019-2020) was submitted to GPCB dated 28.09.2020. Copy of the same is attached herewith as an Annexure H .
(vi)	The criteria pollutant levels namely; PM _{2.5} , PM ₁₀ , SO ₂ , NO _x (ambient levels) or critical sectoral parameters, indicated for the project shall be monitored and displayed at a convenient location near the main gate of the company in the public domain.	The criteria pollutants levels namely PM _{2.5} , PM ₁₀ , SO ₂ , NO _x (ambient levels) are being monitored regularly through M/s. Kadam Environment Consultant, Baroda. In addition to this, Online Continuous Emission Monitoring System had been installed and data is being displayed on display board at main gate of the company.
(vii)	The project proponent shall inform the Regional Offices as well as the Ministry, the date of financial closure and final approval of the project by the concerned authorities, commencing the land development work and start of production operation by the project.	Noted.
(viii)	The project authorities must strictly adhere to the stipulations made by the State Pollution Control Board and the State Government.	Noted and agreed.
(ix)	The project proponent shall abide by all the commitments and recommendations made in the EIA/EMP report, commitment made during Public Hearing and also that during their presentation to the Expert Appraisal Committee.	Noted and agreed.

()	I NI. C. d	NI. (I
(x)	No further expansion or	Noted.
	modifications in the plant	
	shall be carried out without	
	prior approval of the Ministry	
	of Environment, Forest and	
	Climate Change (MoEF&CC).	
(vi)		Noted.
(xi)		Noteu.
	submission of false/fabricated	
	date may result in revocation	
	of this environmental	
	clearance and attract action	
	under the provisions of	
	Environment (Protection) Act,	
	1986.	
(xii)		Noted.
(////	suspend the clearance, if	Noted.
	implementation of any of the	
	above conditions is not	
	satisfactory.	
(xiii)		Noted and agreed.
	right to stipulate additional	
	conditions if found necessary.	
	The company in a time bound	
	manner shall implement	
	these conditions.	
(xiv)		Noted and agreed.
(//	Ministry shall monitor	Trottod dina dgroodi
	compliance of the stipulated	
	·	
	· ,	
	authorities should extend full	
	cooperation to the officer (s)	
	of the Regional Office by the	
	furnishing the requisite	
	data/information/monitoring	
	reports.	
(xv)	The above conditions shall be	Noted.
` ′	enforced, inter-alia under the	
	provisions of the Water	
	(Prevention & Control of	
	Pollution) Act, 1974, the Air	
	(Prevention & Control of	
	Pollution) Act, 1981, the	
	Environment (Protection) Act,	
	1986, Hazardous and Other	
	Wastes (Management and	
	Transboundary Movement)	
	Rules, 2016 and the Public	
	Liability Insurance Act, 1991	
	along with their amendments	
	and Rules and any other	
	order passed by the Hon'ble	
	Supreme Court of India/High	
	Courts and any other Court of	
1		
	Law relating to the subject matter.	

(xvi)	Any appeal against this EC	Noted.
	shall lie with the National	
	Green Tribunal, if preferred,	
	within a period of 30 days as	
	prescribed under Section 16	
	of the National Green	
	Tribunal Act, 2010.	